

BUTTERFLY Urinal

Design: Sam Gullam



The Butterfly Urinal meets the demands in the city centres when priority is a hygienic and clean On-Street Urinal.

Connection to water, electricity and sewerage gives a smell free solution all year around and the self-flushing system makes the urinal hygienic.

The Butterfly contains two cubicles and is built of entirely stainless steel, to a contemporary design.

The units have a small footprint, making them ideal for use on the narrow pavements of the city. Their sleek profile is designed to achieve minimum disruption to the line of pedestrian flow.



TECHNICAL INFORMATION BUTTERFLY

GENERAL INFORMATION

Each Urinal is connected to water, sewerage and electricity, and is self-flushing. The user benefits from a discreet partial enclosure that provides a clean, safe and easily accessible toilet facility.

The Urinal opens during the night and is a successful system in reducing street fouling.

Our toilet buildings are delivered pre-fabricated for installation on a foundation prepared by the client. Danfo supplies all the drawings and technical specifications needed to make a planning permission application together with a proposal for a foundation.

SERVICE AND MAINTENANCE

The On-Street Urinal, like all Danfo products, is available either by capital purchase or on lease terms. It can also be packaged with the Sanirent® Concept.



Within the Sanirent® concept, Danfo take care of daily cleaning and maintenance and always ensuring that the visitors enters a clean and hygienic, high standard toilet facility.

FOUNDATION AND FRAMEWORK

Foundation

The concrete beams of the urinal form part of the foundation.

Walls and Ceiling

Walls and ceiling are made of insulated stainless sheet with broomed surface and insulation.

Floor

The concrete slab is covered by an acid-proof stainless steel floor.

Doors

The doors are made of decorated designed stainless steel.

INSTALLATION

Sanitation

Ø 25mm water intake. Plastic drainpipe 75 mm connection. Filter in drain sink for easy cleaning. Anit-freezing heating cables fitted to all water pipes.

Electricity

Distribution box with automatic fuses and earth fault breaker. Control system for automatic functions. Long life light fittings.

MEASUREMENTS

Closed position:

Length 1670mm, width 674mm, height 2240mm

Open position:

Length 1731mm, width 861mm, height 2240mm



These details are subject to changes in design.